

PRO SERIES VPRO-NVR-8-U

8-ch 1 HDD Network Video Recorder



Features

- Support Ultra 265/H.265/H.264 video formats
- 8-channel input
- Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T
- Support HDMI and VGA simultaneous output
- Up to 4K resolution recording
- 1 SATA HDD up to 10TB
- Support cloud upgrade

Specifications

VIDEO/AUDIO INPUT	
IP Video Input	8-ch
Two-way Audio Input	1-ch, RCA
NETWORK	
Incoming Bandwidth	64Mbps
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
VIDEO/AUDIO OUTPUT	
HDMI/VGA Output	HDMI: 4K (3840x2160@30), 1920X1080@60, 1920X1080@50, 1600X1200@60, 1280X1024@60, 1280X720@60, 1024X768@60 VGA: 1920X1080@60, 1920X1080@50, 1280X1024@60, 1280X720@60, 1024X768@60
Recording Resolution	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	8-ch
Corridor Mode Screen	3/4/5/7/9
DECODING	
Decoding format	Ultra 265, H.265, H.264
Live view/ Playback	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30
HARD DISK	
SATA	1 SATA interface
Capacity	Up to 10TB
EXTERNAL INTERFACE	
Network Interface	1 RJ-45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 1 x USB3.0

PRO SERIES VPRO-NVR-8-U

8-ch 1 HDD Network Video Recorder



GENERAL

Power Supply	12V DC Power Consumption: $\leq 8W$ (without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity $\leq 90\%$ RH (non-condensing)
Dimensions(W×D×H)	260mm × 240mm × 47mm (10.2"×9.4"×1.9")
Weight (without HDD)	1.3kg (2.87lb)