

VL-EXT8231-XX

Explosion proof Spot Light



Key Features

- Input Voltage: AC 100-270 v
- PF>0.95 CRI: Ra>75
- Protection Grade: IP66
- Lumen Flux: 120lm/w
- Anti Corrosion: WF2
- Weight: 3.8 kg / 8.3 lbs
- Size: 230 x 166 mm / 9 x 6.5 in
- Beam Angle: 14°
- Ex-proof Grade: ExdIICT6

MODEL	VOLTAGE
VL-EXT8231-50W	50W
VL-EXT8231-60W	60W
VL-EXT8231-80W	80W
VL-EXT8231-90W	90W

Rated Voltage	AC100-270V
Power	50-90w
Frequency	50/60 hz
Light Efficiency	120 lm
Power Factor	>0.95 pf
Operating Temperature	-30~50 °C / -22~122 °F
Storage Temperature	-30~50 °C / -22~122 °F
Protection Level	IP66
Lighting Angle	20/60/90 °
Light Source	led
Correlate Color Temperature	3000-6500 k
Color Rendering Index	≥70 ra
LED Qty	80 pcs
Base Specifications	CREE3030
LED'S Operating Life	100000 h
Start-Up Time	≤0.2 s
Anti-Corrosion Grade	WF2
Explosion Proof Grade	Exd IIC T6 Gb
Executive Standard	GB3836.1 / GB3836.2
Weight	3.8 kg / 8.3 lbs
Size	230 × 166 mm / 9 × 6.5 in

Dimensions

