

EX LIGHTING VL-EX8260MD

LED Explosion-proof Flood Medium Sized Light



Features:

- Configuration: It adopts imported LED light source, with an average service life of up to 100,000 hours. The power supply adopts wide voltage processing, which can realize constant current output, and has short-circuit and over-voltage protection functions, which greatly prolongs the service life of the lamps.
- Heat dissipation: explosion-proof electrical box and lamp holder double cavity design, large space size to ensure the assembly of various large-scale electrical appliances. Excellent heat dissipation performance, so that the LED chip and power supply temperature rise is reasonably controlled within a reasonable range, greatly ensuring the service life of the lamp.
- Light distribution: light projection is even and soft, especially suitable for all kinds of need to cast light, floodlights as a fixed lighting.
- Protection: The protection level of the lamp body is IP66, and the anti-corrosion level can reach WF2. The surface of the lamp body will never corrode and never rust.
- Installation method: Various installation methods such as ceiling, suction wall and U-shaped anti-vibration bracket (angle adjustable) can be used as needed.

Specifications:

Rated Voltage	100-220VAC
Power	80-190W
Protection Level	IP66
Lighting Angle	110°
LED Qty	180 pcs
Base Specifications	CREE3030
Anticorrosion Grade	WF2
Explosion Proof Grade	Ex demb IIC T6
Light Efficiency	T6
Frequency	120 Lm/W
Power Factor	50/60 Hz
Operating Temperature	>0.95 PF
Storage Temperature	-30°C ~ 50°C
Light Source	-30°C ~ 50°C
Correlate Color Temperature	LED
Color Rendering Index	3000-6500 K
LED's Operating Life	≥70 Ra
Start-Up Time	100000s
Executive Standard	≤0.2s
Weight	6.7 Kg
Size	374×276×171 (mm)

Dimensions:

