

Explosion proof Long Hanging Lamp



Features

- Input Voltage: AC100-270v
- Led Source: Cree
- PF>0.95 CRI: Ra>75
- Protection Grade: IP66
- Lumen Flux: 120 lm/w
- Anti Corrosion: WF2
- Weight: 6.4 kg / 14.1 lbs
- Size: 230 x 307 mm / 9 x 12 in
- Beam Angle: 141.9°
- Ex-proof Grade: ExdIICT6

MODEL	VOLTAGE
VL-EXLG8231-50	50W
VL-EXLG8231-60	60W
VL-EXLG8231-80	80W
VL-EXLG8231-90	90W

VIDEO INPUT	
Rated Voltage	AC100-270V
Power	50-90 w
Frequency	50/60 hz
Light Efficiency	120 lm
Power Factor	>0.95 pf
Operating Temperature	-30~50 °C
Storage Temperature	-30~50 °C
Protection Level	IP66
Lighting Angle	140 °
Light Source	led
Correlate Color Tem- perature	3000-6500 k
Color Rendering Index	≥70 ra
LED Qty	45 pcs
Base Specifications	CREE3030
LED'S Operating Life	100000 h
Start-Up Time	≤0.2 s
Anti-Corrosion Grade	WF2
Explosion Proof Grade	ExdIICT6
Executive Standard	GB3836.1 / GB3836.2
Weight	6.4 kg / 14.1 lbs
Size	230 x 307 mm / 9 x 12 in

Dimensions

