

# SVEX-H20

Explosion proof dome camera housing



**VEILUX**<sup>®</sup>  
*The Art of Surveillance*



Specifications	
Atmospheric Pressure	80 kPa 106 kPa
Operating Ambient Temp	-25°C to 60°C (-13°F to 140°F)
Relative Humidity	5 % to 95 % nocondensing
Protection rating	<ul style="list-style-type: none"><li>● Ex d IIC T6 Gb Explosin-proof marking</li><li>● IP68, NEMA-4X enclosure rating</li></ul>
Dimensions ( Ø x H )	( 204x 446 mm ) ( 8.03 x 17.56 In )
Internal Usable Size	-
Window Viewing Area ( Ø )	-
Weight	12 Kg ( 26.25 lb )
Material	<ul style="list-style-type: none"><li>● AISI 304 stainless steel 2MEXH-20</li><li>● AISI 316L stainless steel 2MEXH-20-L</li></ul>

## Model :

SVEX-H20: IP68 explosion proof dome camera housing

## Available models :

Model	Material
2MEXH-20	AISI 304 stainless steel
2MEXH-20-L	AISI 316L stainless steel

## Features :

- IP68, NEMA-4X Enclosure rating
- Operating temperature range from -25°C to 60°C (-13°F to 140°F)
- Ex d IIC T6 Gb explosion-proof marking
- AISI 304/316L stainless steel construction (available)