

# V-ARMOR SERIES SVEX-HQ

Explosion proof high speed dome



ELECTRICAL	
<b>Input Voltage</b>	AC100-24°V/AC 24V
<b>Power</b>	<50W
<b>Communication Mode</b>	RS-485
<b>Communication Agreement</b>	Pelco-D Pelco-P According to Client's Demands
PHYSICAL	
<b>Net weight</b>	12Kg
<b>Material</b>	SS304 (chemical factories, outdoors and so on) SS316L (sea environment, oil tankers and so on ) (Optional)
<b>Auto-heated</b>	While it is <1°c (Optional)



## Key Features

- Stainless steel 304 or 316L
- Optional electro-polished or corrosion resistant paint finish
- IP68, dust tight, protect against continuous immersion in water
- Consists of optical high speed dome camera
- Variable speed: 0.1° ~ 40°/s
- Indoor, outdoor installation
- High resolution: Up to 2MP
- Applicable for high corrosive circumstances
- Applicable for temperatures -13°F ~ 140°F (-25°C ~ 60°C)

Specifications	SVEX-HQ30
<b>Ex proof marking</b>	Exd CT6 Gb/Ex td A21,T6
<b>Enclosure protection</b>	IP68
<b>Vertical and Horizontal speed</b>	0.1°/s ~ 400°/s
ENVIRONMENTAL	
<b>Air pressure</b>	86~106KPa
<b>Temperature</b>	-40°F ~ 60°F (-40°C ~ +16°C)
<b>Humidity</b>	<95%RH [77°F (+25°C)]

## Dimensions

