

PRO SERIES VBIP-2-BZ-PRO-Q

2MP Motorized Network Bullet Camera with IR up to 70m



Features

- 1/2.7" Progressive scan CMOS Sensor
- Motorized lens, 2.7~13.5mm
- Up to 70m IR distance
- Basic and smart event features
- POE
- IP67

CAMERA	
Image Sensor	1/2.7" Progressive scan CMOS Sensor
Min. Illumination	0.006lux (Color), 0lux (IR on)
Illuminator Number	4 (IR light)
Illumination Distance	70m (IR light)
Strobe Light	Supported
Smart Light	Supported
Pan/Tilt/Rotation Range	Pan: 0°~360° Tilt: 0°~90° Rotation: 0°~360°
LENS	
Focal Length	2.7-13.5mm
Aperture	F1.6
FOV	horizontal FOV:112° to 35.5°, vertical FOV:59° to 20°, diagonal FOV Ø134° to 41°
Lens Mount	Ø14
COMPRESSION STANDARD	
Video Compression	H.264/H.265/264+/265+/MJPEG
H.264 Codec Profile	Base/Main/High profile
H.265 Codec Profile	Main profile
Video Bit Rate	11 Kbps~8 Mbps
Triple Streams	NA
Audio Compression	G.711A(-A Model), G711U
Audio Bit Rate	64 Kbps(-A Model)
IMAGE	
Max. Image Resolution	5M(2880 × 1620)
Main Stream	50Hz: 20fps 5MP(2880 × 1620) 25fps 4MP(2688 × 1520) 25fps 4M(2560 × 1440) 25fps 1080P(1920 × 1080) 60Hz: 20fps 5MP(2880 × 1620) 30fps 4MP(2688 × 1520) 30fps 4M(2560 × 1440) 30fps 1080P(1920 × 1080)
Sub Stream	50Hz: 25fps 720P(1280 × 720) 25fps D1(704 × 576),25fps CIF(352 × 288) 60Hz: 30fps 720P(1280 × 720) 30fps D1(704 × 480),30fps CIF(352 × 240)
Third Stream	NA
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
Shutter Time	Auto/Manual, 1/3~1/100000s
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	120dB
Digital noise reduction	2D/3D DNR
BLC	Supported
HLC	Supported
ROI	Supported
Rotate	Supported

PRO SERIES VBIP-2-BZ-PRO-Q

2MP Motorized Network Bullet Camera with IR up to 70m



SMART FEATURES	
Basic Event	Motion detection (human and vehicle targets classification), Video Shelter
Smart Event	Line Crossing , Area Intrusion (supports alarm triggering by specified target types (human and vehicle))"
Face Detection	NA
NETWORK	
Network Storage	NAS (NFS, SMB/CIFS), ANR
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P
System Compatibility	Onvif (Profile S, Profile G, T), SDK
Security	Password protection, complicated password, HTTPS encryption, IP address filter, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2, WSSE and digest authentication for Open Network Video Interface
Web Browsers	Plug-in required live view: IE 10, IE 11 Local service: Chrome 57.0+, Firefox 52.0+
User	Up to 10 users
INTERFACE	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
On-board Storage	up to 256GB
MIC	Supported
Speaker	NA
Audio I/O	NA
Alarm I/O	NA
Reset Button	Supported
GENERAL	
Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
Power Supply	DC12V $\pm$ 10%
POE	PoE (802.3af)
Power Consumption	MAX.9W
Protection Level	IP67
Material	Metal
Dimensions	Ø76X215.8 mm
Gross Weight	980g