

VBIP-2V-H5Z-N

2MP IR Motorized Bullet Network Camera



VEILUX[®]
The Art of Surveillance



Features:

- 1/2.8" progressive scan CMOS
- Max. 2MP(1920 x 1080) @30fps resolution
- 2.7~13.5mm motorized lens
- WDR, 3D DNR, ROI, HLC, BLC
- 1/1 audio in/out, 1/1 alarm in/out
- Smart IR up to 60m
- Built-in micro SD slot
- IP67, IK10
- PoE

Specifications:

CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS
Effective Pixels	1920(H) × 1080(V)
Electronic Shutter	1/5 ~ 1/20,000s
Min. Illumination	Color: 0.001Lux @(F1.2, AGC ON) B/W: 0Lux @(IR LED ON)
S/N Ratio	55dB
Day/Night	ICR
Wide Dynamic Range	True WDR
IR Range	Up to 60m (196.9 ft)
IR On/Off Control	Auto/ Manual
Pan/Tilt/Rotation Range	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360°
LENS	
Lens Type	Motorized
Iris	Fixed Iris
Focal Length	2.7 ~ 13.5mm
F Number	F1.6
Angle of View	H: 95° ~ 28.4°, V: 50.3° ~ 15.9°
VIDEO	
Max. Resolution	1080P(1920 × 1080)
Streaming Capability	3 Streams
Stream / Frame Rate	Stream1: 1920 × 1080/1280 × 720 @25/30fps Stream2: D1/VGA/640 × 360/CIF/QVGA @25/30fps Stream3: VGA/CIF/QVGA @25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 100kbps ~ 12Mbps Stream2: 10kbps ~ 6Mbps Stream3: 10kbps ~ 3Mbps
Image Enhancement	HLC/BLC/Anti-shake/WDR
White Balance	Supported
Gain Control	Auto/Manual
Noise Reduction	2D/3D DNR
Smart IR	Supported
Mirror	Supported
Region of Interest	Supported
Motion Detection	Supported
Privacy Masking	Supported
AUDIO	
Compression	G.711, RAW_PCM
Bit Rate	8kbps, 16kps, 64kbps
NETWORK	
Protocols	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTT, PPPoE, SMTP, DNS, UPnP, FTP, ARP, SNMP, TLS/SSL
Interoperability	ONVIF, SDK, CGI
Streaming Method	Unicast
Max. User Access	10 Users
Web Viewer	<IE*11, Chrome®, Firefox®

VBIP-2V-H5Z-N

2MP IR Motorized Bullet Network Camera



VEILUX®
The Art of Surveillance

INTERFACE	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio	1ch Input, 1ch Output
Alarm	1ch Input, 1ch Output
Reset Button	Supported
Storage	Built-in Micro SD slot, up to 256GB
ELECTRICAL	
Power Supply	DC12V/POE (IEEE 802.3af)
Power Consumption	Max 10.5W
Operating Temperature	-40°C ~ 55°C (-40°F ~ 131°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP67, IK10
Certifications	CE/FCC
Casing	Metal
Dimensions	Ø 110 x 375.5 (mm)/Ø 4.33" x 14.78" (in.)
Net Weight	1.45 kg (3.2 lbs)

Note: Design and specifications are subject to change without notice.

Dimensions:

