

V-WEB SERIES VIPR-3M30X-PRO

3MP High Speed PTZ Vandal Proof Camera with 30X Zoom



Key Features

- 1/2.8" Progressive Scan CMOS
- 30X Optical Zoom, 16X Digital Zoom
- 2048(H) x 1536(V)/25fps
- Multiple Streams
- Low bitrate, good low-light performance
- 2D/3D DNR, ICR, WDR > 100dB
- Anti-Bloom Technology
- Video Signal-to-Noise > 50 dB
- BLC (Back Light Compensation)

Specifications	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.01 Lux; B&W: 0.001 Lux; IR ON 0 Lux, PAL/NTSC
Day & Night	ICR
Shutter Speed	1/10,000-1/1s
Auto Iris	Auto/Manual
Wide Dynamic Range	WDR >100db
Digital Noise Reduction	2D/3D (On/Off Selectable)
AWB	Yes
Lens	30x Module, 4.3 - 129 mm
Pan/Tilt Speed	Pan: 0.05° - 350°/s; Tilt: 0.05°-350°/s
Pan/Tilt Angle	Pan: 360° endless, Tilt: 180°
Digital Zoom	16X
FOV	70.5" - 3.2"
Electric Shutter	Selectable ON/OFF
Auto Gain Control (AGC)	Switchable ON/OFF
IMAGE	
Video Compression	H.264 Hi-light/Baseline Profile, MJPEG
Bit Rate (CBR/VBR)	100 kb - 12,000kb
Fram Rate	30fps at Full Resolution
Audio Compression	G.711, RAW_PCM
Max. Resolution	2048 x 1536/30fps
Stream	Stream 1: 2048 x 1536 Stream 2: 1080P / 720P / D1 / CIF / QCIF / VGA / 640 x 360
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
HLC/BLC	Yes
ROI	Yes
Defog	Yes
NETWORK	
Network Protocols, Open IP Standards	HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, PPoE, Unicast and Multicast Supported
Alarm Trigger	Motion, Intrusion, Line Crossing, Tamper, Network Disconnect, Disk Alarm, I/O Alarm
RTSP Video	Standard RFC2326, Support Quick Time/VLC Player
Security	User Security Authentication, Reset, Hardware, WatchDog
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish
System Compatibility	Onvif, CGI

V-WEB SERIES VIPR-3M30X-PRO

3MP High Speed PTZ Vandal Proof Camera with 30X Zoom



Optional Mounts:



In-Ceiling Mount



Pendant Mount

INTERFACE	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio I/O	1ch Audio In & 1ch Audio Out
Alarm I/O	7ch Alarm In & 2ch Alarm Out
RS485	Yes
BNC Output	Yes
Reset Button	Yes
Edge Storage	Micro SD/SDHC/SDXC Slot, Max 64GB
Power Supply	AC24V / 2.5A
Power Consumption	Max 40W
Operating Temperature	-40°C ~+70°C with Heater
Operating Humidity	0%-90% RH
Ingress Protection	IP-66, TVS6000V, IK10
Approvals	CE / FCC
Product Dimensions	368 x 278 (mm)
Product Weight	43kg (9.48 lbs)

Dimensions

