

PRO SERIES VPIP-2MIR25X-150-POE-U



2MP Network Pan Tilt Zoom Camera with IR up to 100m and 25x Zoom



Features

- 1/2.8" progressive scan CMOS
- 25X Optical Zoom/ 16X Digital Zoom 4.7~118mm
- Up to 100m IR distance
- POE
- IP66

CAMERA	
Image Sensor	1/2.8" Progressive scan CMOS Sensor
Min. Illumination	0.006 lux (ICR ON, AGC ON)
IR	7pcs Array LED, 3pcs Laser light
IR Range	100m
Smart IR	Support
Shutter Time	Auto/Manual, 1/3~1/10000s
Slow Shutter	Support
Day/Night	IR cut filter with auto switch
Wide Dynamic Range	120dB WDR
Digital noise reduction	2D/3D DNR
Starlight	Support
Lens	25X Optical Zoom/ 16X Digital Zoom 4.7~118mm
Aperture Range	F1.5 (W)~F3.2 (T)
PAN & TILT	
Pan Range	360°endless
Pan Speed	1°~70°/s
Tilt Range	-10°~90° (Auto Flip)
Tilt Speed	1°~35°/s
Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples
Number of Preset	255
Power Loss Recovery	Support
Patrol	32 automatic Patrols
Pattern	8 patterns
COMPRESSION STANDARD	
Video Compression	H.264/H.264+/H.265/H.265+
H.264 Codec Profile	Base/Main/High profile
H.265 Codec Profile	Main profile
Video Bit Rate	11 Kbps~8192Kbps
Triple Streams	Support
Audio Compression	G.711A/G.711U
Audio Bit Rate	64 Kbps
IMAGE	
Max. Image Resolution	1080P(1920 × 1080)
Frame Rate	50Hz: 25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 720P(1280 × 720) 60Hz: 30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960), 720P(1280 × 720)
Sub Stream	50Hz: 25fps D1(704 × 576), 25fps CIF(352 × 288) 60Hz: 30fps D1(704 × 480), 30fps CIF(352 × 240)*
Third Stream	50Hz: 25fps CIF(352 × 288) 60Hz: 30fps CIF(352 × 240)
Image Setting	Brightness/Contrast/Saturation/Hue/Sharpness
BLC	On/Off, zone configurable

PRO SERIES VPIP-2MIR25X-150-POE-U



2MP Network Pan Tilt Zoom Camera with IR up to 100m and 25x Zoom

ROI	Supported
Defog	Supported
NETWORK	
Network Storage	NAS(NFS/CIFS),ANR
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour
Event	Motion Detection, Video Shelter
Smart Functions	Line Crossing, Area Intrusion, Unattended Object, Object Missing, Region Entrance, Region Exiting, Fast Moving
System Compatibility	Onvif 2.4, Profile S, CGI
Security	User authentication, IP address filtering, Video mask
Mobile Surveillance	iPhone, iPad, Android devices
INTERFACE	
Communication interface	1 RJ45 10M / 100M Ethernet Port
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128GB
Audio I/O	1/1
Alarm I/O	1/1
GENERAL	
Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
Power Supply	DC 12V
POE Supply	PoE (802.3at)
Power Consumption	MAX 15W
Weather Proof	IP66
Protection	6000V lightning protection, surge protection and anti-surge protection
Material	Aluminum-Alloy
Dimensions	185.0×375.0(mm)
Gross Weight	4.5KG

Dimensions

