

V-ARMOR SERIES VPIP-3MIR30X-H5



H.265/H.264 3MP Network IR High Speed Dome Camera



Key Features

- 1/2.8" Progressive Scan CMOS
- 30X Optical Zoom, 16X Digital Zoom
- 2048(H) × 1536(V)/30fps
- Multiple Streams
- Smart IR Range 150m
- Low bitrate, good low light performance
- 3D DNR, dWDR, ICR
- Anti-reflection optical glass to increase infrared transmittance

Specifications	VPIP-3MIR30X-H5
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Day & Night	ICR
Shutter Speed	1/1 - 1/10000s
Auto Iris	Auto/Manual
Wide Dynamic Range	dWDR
Digital Noise Reduction	3D
Lens	30X Module , 4.3-129mm
Digital Zoom	16X
FOV	59.8°~2.3°
IR LED	8 pcs
IR Range	150m
Pan/Tilt	Pan 0-360°, Tilt -10-90°
Pan/Tilt Speed	Pan: 0.01°/s ~ 180°/s , Tilt: 0.01°/s ~ 90°/s
Preset Speed	Pan: 180°/s , Tilt: 90°/s
3D Position	YES
Coordinate Display	YES
Preset/Tour/Scan/Track	400/12/12/6
Image	
Video Compression	H.265, H.264 High/Main/Baseline Profile, MJPEG
Bit Rate (CBR/VBR)	Main stream: 500kbps~12Mbps; Sub stream: 100kbps~4Mbps
Audio Compression	256 Kbps-16Mbps
Max. Resolution	2048x1536/30fps
Stream	Stream1 2048x1536, 1920x1080, 1280x720 Stream2 D1/CIF/QCIF/VGA/QVGA/640x360

Image (Cont.)	
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
HLC	Yes
ROI	Yes
Defog	Yes
Network	
Network Protocols	IPv4/IPv6, RTSP/RTP/RTCP/TCP/UDP, HTTPS, DHCP, DNS, DDNS, PPPoE, SMTP
Alarm Trigger	Network disconnect, Disk alarm, I/O alarm
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player
Security	User security authentication, Reset, Hardware WatchDog
Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish
System Compatibility	Onvif, GB, T28181
Interface	
Ethernet	I1 Ethernet (10/100 Base-T) RJ-45 Connector
Audio I/O	1ch Audio In, 1ch Audio Out
Alarm I/O	7ch Alarm In, 2ch Alarm Out
RS485	YES
BNC Output	YES
Reset Button	YES (Built-In)
Edge Storage	Micro SD/SDHC/SDXC slot (Built-in), Max 128GB
GENERAL	
Power Supply	AC24V/2.5A
Power Consumption	MAX 40W
Operating Temperature	Starting Temperature: -30°C~60°C (-22°F~140°F) Working Temperature: -40°C~60°C (-40°F~140°F)
Operating Humidity	0% - 90% RH
Protection	IP66, TVS4000V
Approvals	CE / FCC
Product Dimensions	Ø205x332mm
Product Weight	4.35KG

Dimensions

