

# PRO SERIES VPIP-6M25X-100-PRO-Q

6MP Network Pan Tilt Zoom Camera with IR up to 100m and 25x Zoom



## Features

- 1/2.8" progressive scan CMOS
- 25X Optical Zoom/ 16X Digital Zoom 4.7~118mm
- Up to 100m IR distance
- POE
- IP66

CAMERA	
<b>Image Sensor</b>	1/2.8" Progressive scan CMOS Sensor
<b>Min. Illumination</b>	0.006 lux (ICR ON, AGC ON)
<b>IR</b>	7pcs Array LED, 3pcs Laser light
<b>IR Range</b>	100m
<b>Smart IR</b>	Support
<b>Shutter Time</b>	Auto/Manual, 1/3~1/10000s
<b>Slow Shutter</b>	Support
<b>Day/Night</b>	IR cut filter with auto switch
<b>Wide Dynamic Range</b>	120dB WDR
<b>Digital noise reduction</b>	2D/3D DNR
<b>Starlight</b>	Support
LENS	
<b>Lens</b>	25X Optical Zoom/ 16X Digital Zoom 4.7~118mm
<b>Aperture Range</b>	F1.5 (W)~F3.2 (T)
PAN & TILT	
<b>Pan Range</b>	360°endless
<b>Pan Speed</b>	1°~70°/s
<b>Tilt Range</b>	-10°~90° (Auto Flip )
<b>Tilt Speed</b>	1°~35°/s
<b>Proportional Zoom</b>	Rotation speed can be adjusted automatically according to zoom multiples
<b>Number of Preset</b>	255
<b>Power Loss Recovery</b>	Support
<b>Patrol</b>	32 automatic Patrols
<b>Pattern</b>	8 patterns
COMPRESSION STANDARD	
<b>Video Compression</b>	H.264/H.264+/H.265/H.265+
<b>H.264 Codec Profile</b>	Base/Main/High profile
<b>H.265 Codec Profile</b>	Main profile
<b>Video Bit Rate</b>	11 Kbps~8192Kbps
<b>Triple Streams</b>	Support
<b>Audio Compression</b>	G.711A/G.711U
<b>Audio Bit Rate</b>	64 Kbps
IMAGE	
<b>Max. Image Resolution</b>	1080P(1920 × 1080)
<b>Frame Rate</b>	50Hz: 25fps 1080P(1920 × 1080) 25fps 960P(1280 × 960), 720P(1280 × 720) 60Hz: 30fps 1080P(1920 × 1080) 30fps 960P(1280 × 960), 720P(1280 × 720)
<b>Sub Stream</b>	50Hz: 25fps D1(704 × 576), 25fps CIF(352 × 288) 60Hz: 30fps D1(704 × 480), 30fps CIF(352 × 240)"
<b>Third Stream</b>	50Hz: 25fps CIF(352 × 288) 60Hz: 30fps CIF(352 × 240)
<b>Image Setting</b>	Brightness/Contrast/Saturation/Hue/Sharpness
<b>BLC</b>	On/Off, zone configurable

# PRO SERIES VPIP-6M25X-100-PRO-Q

6MP Network Pan Tilt Zoom Camera with IR up to 100m and 25x Zoom



<b>ROI</b>	Supported
<b>Defog</b>	Supported
<b>NETWORK</b>	
<b>Network Storage</b>	NAS(NFS/CIFS), ANR
<b>Protocols</b>	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NT, IGMP, UPnP, SMTP, UPnP-TM, P2P, Bonjour
<b>Event</b>	Motion Detection, Video Shelter
<b>Smart Functions</b>	Line Crossing, Area Intrusion, Unattended Object, Object Missing, Region Entrance, Region Exiting, Fast Moving
<b>System Compatibility</b>	Onvif 2.4, Profile S, CGI
<b>Security</b>	User authentication, IP address filtering, Video mask
<b>Mobile Surveillance</b>	iPhone, iPad, Android devices
<b>INTERFACE</b>	
<b>Communication interface</b>	1 RJ45 10M / 100M Ethernet Port
<b>On-board storage</b>	Built-in Micro SD/SDHC/SDXC slot, up to 128GB
<b>Audio I/O</b>	1/1
<b>Alarm I/O</b>	1/1
<b>GENERAL</b>	
<b>Operating Conditions</b>	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
<b>Power Supply</b>	DC 12V
<b>POE Supply</b>	PoE (802.3at)
<b>Power Consumption</b>	MAX. 15W
<b>Weather Proof</b>	IP66
<b>Protection</b>	6000V lightning protection, surge protection and anti-surge protection
<b>Material</b>	Aluminum-Alloy
<b>Dimensions</b>	185.0 × 375.0 (mm)
<b>Gross Weight</b>	4.5KG

## Dimensions

