


VPRO-NVR-64-8HD-Q



NDA A 2019 complaint means this product does not contain HiSilicon chipsets. HiSilicon is manufactured by telecom company Huawei. The U.S. federal government banned Huawei products from all its facilities to mitigate its security risk.

Features

- Ultra 265/H.265/H.264 video formats
- 64 channel input
- 8 HDDs, up to 20TB for each HDD
- Front panel: 2 × USB 2.0, Rear panel: 1 × USB 3.0
- RS485 x2
- Alarm In: 16-ch, Alarm Out: 4-ch
- Supports Raid 0, 1, 5, 10

VIDEO & AUDIO INPUT	
Chipset	NT98336-E
IP Video Input	64ch
Audio input	1-ch, RCA
VIDEO & AUDIO OUTPUT	
HDMI	HDMI 1: 4K(3840×2160)/30Hz, 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz HDMI 2: 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz"
VGA	1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz
Audio Output	2-ch, RCA
RECORDING	
Compression	H.265+/H.265/H.264+/H.264
Resolution	12MP/8MP/5MP/4MP/3MP/1080P/720P/D1/CIF/QCIF
PLAYBACK & BACKUP	
Playback Resolution	12MP/8MP/5MP/4MP/3MP/1080P/720P/D1/CIF/QCIF
Decoding Capability	2ch@12M 20fps 4ch@8M 30fps 6ch@5M 30fps 8ch@4M 30fps 16ch@1080P 30fps
Synchronous Playback	16ch
Playback Mode	Smart Playback/Normal/Time Division/Label/Event/Picture Playback
Backup Mode	USB Device/Network/eSATA
ADVANCED FEATURES	
Smart Detection by Camera	Area Intrusion, Line crossing, Region Entrance/Region Exiting, Fast Moving, Object Missing, Unattended Object, Loitering Detection, Parking Detection, Face Detection, People Gathering Detection, Blurred detection, Scene change detection, Audio exception detection, SMD, PP
Smart Playback	Face detection/Line Crossing/Area Intrusion/Motion Detection/ Human Detection/Vehicle Detection
Cloud Storage	Supported
Cloud Upgrade	Supported
NETWORK	
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	256Mbps
Ethernet	2 × RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Network Function	HTTPs, HTTP, TCP/IP, IPv4, UPnP, RTSP, UDP, SMTP, SNMP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, ONVIF
Smart Phone	IOS (iPhone, iPad), Android (Phone, Pad)
HARD DISK	
SATA	8 SATA interface
Capacity	Up to 20TB capacity for each HDD
RAID	Supports Raid 0, 1, 5, 10
EXTERNAL INTERFACE	
USB Interface	Front panel: 2 × USB 2.0 Rear panel: 1 × USB 3.0
eSata	1x eSATA
RS485	2
Alarm In	16-ch
Alarm Out	4-ch

PRO SERIES VPRO-NVR-64-8H

64 Channel Network Video Recorder with 8 HDD



GENERAL	
Power Supply	AC 100~240V
Power Consumption	≤20W(without HDD)
Working Environment	0°C~+55°C / 10%~90%RH
Dimension (W×D×H)	440×452×90mm
Weight	7.9kg