


V-RECON SERIES VV-2HDIR24Z-4N1-S

2.4MP High Resolution Vandal Proof IR Motorized Dome Camera



Key Features

- 1/2.8" 2.4MP Sony CMOS Sensor
- Lens: Equipped with 3 Axis Lens
- Motion Detection
- Privacy Mask Function
- 2.8-12mm TDN DC Iris (Auto Iris) Motorized Lens, Auto Focus
- True Day & Night (ICR)
- Video Output: AHD / TVI / CVI / CVBS
- Built-in IR LED 24pcs (Night View Distance up to 30m)
- External Control (Focus / Zoom, OSD)
- Service Video Controller through Cable
- Transmission Distance: Upt o 200m via Coaxial Cable (RG59)

Specifications	
Image Sensor	1/2.8" 2.4 Mega Pixel Sony CMOS Sensor
Scanning System	Progressive
Resolution	Digital: 1920Hx1080P, Analog: 1300 TVL NTSC / PAL
Total Pixels	2000(H) x 1241(V) = 2.48 M pixel
Active Pixels	1984(H) x 1225(V) = 2.43 M pixel
Shutter Speed	Auto/ Manual (1/50(1/60) ~ 1/100,000)
Min. Illumination	0.003 Lux (Color) (0 Lux IR LED ON)
S/N Ratio	>50dB (AGC off)
AGC	1 - 5 Levels
Day & Night	Auto/ Color/ B&W/ Ext
White Balance	ATW/ Manual/ AWC Push
Backlight	1 - 16 Levels, BLC
Mirror	Off/ H/ V/ H&V/ Rotate
HLC	On/ Off
OSD Control	Include OSD Control
Picture Functions	WDR (120 dB), HSBLCL, 3DNR, Defog
Privacy Zone	4 Areas
Motion Detection	4 Areas
LSC	On/ Off
Day & Night System	ICR Function
Video Output	AHD/ TVI/ CVI/ CVBS
IR Led	24 Units
Night View Distance	up to 30m
Lens	2.8-12mm TDN DC Iris (Auto Iris) Motorized Lens, Auto focus
Power Consumption	DC12V Less than 150mA
Temperature Operating	14°F to 131°F (-10°C to 55°C)
Temperature Storage	-4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% - 85% RH
IP Rating	IP66
Dimensions (WxDxH)	Ø5.1" x 4.7" (H) [Ø13cm x 12cm(H)]
Unit Weight	1.90 lb (0.861 kg)
Shipping Weight	2.15 lb (0.975 kg)
Certificates	CE, FCC

Veilux Inc

802 Greenview Dr. Suite 200, Grand Prairie TX. 75050 USA
Toll Free: 1-800-510-6528 Direct: (+1) 214 635-4855 Fax: (+1) 214 988-2858
sales@veilux.net www.veilux.net