V-WEB SERIES
VVIP-2V-E-N

2MP IR Varifocal Lens Eyeball Network Camera

VEILUX®
The Art of Surveillance



Key Features

- 1/2.9" progressive scan CMOS
- 2.8~12mm manual lens
- Max resolution 2MP(1920×1080) @ 25/30fps
- Triple streams
- D-WDR, 3D DNR, ROI, HLC, BLC, Aisle mode, Defog and IVS
- Smart IR up to 35m
- PoE, IP66

Specifications

CAMERA	
Image Sensor	1/2.9" Progressive Scan CMOS
Max. Resolution	1920(H)×1080(V)
Electronic Shutter	Auto/Manual, 1/5 ~ 1/20,000s
Min. Illumination	Color: 0.1 Lux @ (F1.2,AGC ON) , B/W: 0 Lux @ (IR LED ON)
S/N Ratio	55 dB
Day/Night	Auto(ICR)/Day / Night
Wide Dynamic Range	D-WDR
IR Range	Up to 35 m (114.8 ft)
IR On/Off Control	Auto/Manual
Pan/Tilt/Rotation Range	Pan: 0˚ ~ 360˚, Tilt: 0˚ ~ 90˚, Rotation: 0˚ ~ 360˚
LENS	
Lens Type	Manual focal
Iris	Fixed Iris
Focal Length	2.8 ~ 12 mm
F Number	F1.6
Angle of View	H: 98.6° ~ 30.6°, V: 51.1° ~ 17.2°
VIDEO	
Streaming Capability	3 Streams
Stream/Frame Rate	Stream1: 1920×1080, 1280×720 @ 25/30fps Stream2: D1, VGA, 640×360, CIF, QVGA @ 25/30fps Stream3: VGA, CIF, QVGA @ 25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Stream1: 200kbps ~ 12Mbps Stream2: 10kbps ~ 6Mbps Stream3: 10kbps ~ 3Mbps
Image Enhancement	HLC/BLC/Anti-shake/Defog
White Balance	Auto/Tungsten/Fluorescent/Daylight/Shadow/Manual
Gain Control	Auto/Manual
Aisle Mode	Support
Noise Reduction	2D/3D DNR
Region of Interest	Off/On (8 Zone, Rectangle)
Motion Detection	Support
Privacy Masking	Support
NETWORK	
Protocols	IPv4/IPv6, RTSP/RTP/RTCP, TCP/UDP, HTTPS, DHCP, DNS, DDNS, PPPoE, UPNP, ICMP, IGMP, FTP, NTP, SMTP, 802.1x, SNMP, TLS/SSL
Interoperability	ONVIF, SDK
Max. User Access	4 Users
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge
INTERFACE	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Reset Button	N/A

Veilux Inc
802 Greenview Dr. Suite 200, Grand Prairie TX. 75050 USA
Toll Free: 1-800-510-6528 Direct: (+1) 214 635-4855 Fax: (+1) 214 988-2858
sales@veilux.net www.veilux.net


REV03062020


V-WEB SERIES
VVIP-2V-E-N

2MP IR Varifocal Lens Eyeball Network Camera

INTELLIGENCE	
IVS	Perimeter, Single Virtual Fence, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad
ELECTRICAL	
Power Supply	DC12V/POE (IEEE 802.3af)
Power Consumption	Max 8 W
Operating Temperature	-35°C ~ 55°C (-31°F ~ 131°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP66
Certifications	CE/FCC
Casing	Metal
Dimensions	Ø 120 x 96mm (Ø 4.72" x 3.78")
Net Weight	0.8 kg

Dimensions





Veilux Inc
802 Greenview Dr. Suite 200, Grand Prairie TX. 75050 USA
Toll Free: 1-800-510-6528 Direct: (+1) 214 635-4855 Fax: (+1) 214 988-2858
sales@veilux.net www.veilux.net

REV03062020