

PRO SERIES VVIP-2V-IZ-40-PRO



2MP Vandal-proof Motorized Network Dome with IR up to 50m



Features

- 1/2.7" Progressive scan CMOS Sensor
- motorized Varifocal lens, 2.7~13.5mm
- Up to 50m IR distance
- Audio 1/1
- Alarm 1/1
- POE
- IP67, IK10 rating

SPECIFICATIONS	
Image Sensor	1/2.7" Progressive scan CMOS Sensor
Min. Illumination	0.006lux(Color), 0lux(IR on)
Lens Type & Focal Length	motorized Varifocal lens, 2.7~13.5mm
FOV	horizontal FOV:110°~38°, vertical FOV:58°~21°, diagonal FOV: 130°~42°
IR Range	50m
Wide Dynamic Range	120dB
Digital Noise Reduction	2D/3D DNR
Video Compression	H.264/H.264+/H.265/H.265+
Frame Rate	Main stream: 5MP/4MP/2MP@(1~30fps) Sub stream: 720P/D1/CIF(1~30fps) Third stream: CIF@(1~30fps)
Smart Function	Smart Motion Detection, Perimeter Protection 2.0, Face Detection
Communication Interface	1 RJ45 10M/100M Ethernet Port
On-board Storage	Micro SD, up to 256GB
Audio I/O	1/1
Built-in Mic	Supported
Alarm I/O	1/1
Reset Button	Supported
Operating Conditions	-30°C ~ 60°C (-22°F ~ 140°F) Humidity 95% or less (non-condensing)
Power Supply	DC12V ±10%
POE Supply	PoE (802.3af)
Power Consumption	MAX. 9W
Weather Proof	IP67
Vandal Proof	IK10
Dimensions	Ø142×113.4 mm
Weight	980g